

INDOOR ANALOG CAMERAS

Analog cameras require a coaxial (analog) cable connection to an IP encoder or videoNEXT server. The models shown here meet basic requirements for most common indoor applications, but many more cameras are available, including 900mhz wireless transmitting, hidden, and other styles and configurations. A wide variety of mounting hardware, decorative, protective, and hidden enclosures are also available.

JVC750

Fixed, indoor color digital CCD camera. 420 TVL resolution, 12VDC/24VAC operation. C-mount for lens (not included). Variety of focal lengths available. Best value indoor camera. SKU: vnxjif420



Pelco Spectra

Ceiling dome, standard size for can light opening. Pan Tilt Zoom, Pelco RS485 control format, supports presets, choice of clear, mirrored, tinted dome. SKU: vnxpid055



Sony EVID100

Highest quality indoor pan tilt zoom optics, Visca RS232 control format supports chaining, presets, auto-focus/ auto iris IR remote. SKU: vnxsed100



Sanyo Door Peephole Camera

Fits 22mm hole, 40-70mm depth. 36mm facia. Fisheye lens, bnc connector. 12VDC operation. SKU: vnxbdp001



8320 Old Courthouse Road, 2nd Floor
Vienna, Virginia 22182
703.903.0227 main ■ 703.749.5326 fax
sales@videonext.com
www.videonext.com